

WPP-350

Buttons	On/Off button, 2 navigation buttons
Display	OLED Display
Printing Mechanism	Direct line thermal printer
Printing Resolution	203 x 203 dpi (8 x 8 dpmm)
Printing Width	72 mm (576 dots)
Printing Speed	80 mm per second
Printable Font Sizes	Font A - 12 x 24 dots, Font B - 9 x 16 dots
Printable Barcode Types	Codabar, Code 128, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, GS1 DataBar Stacked, Omnidirectional, Stacked Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, PDF417, Micro PDF417, QR Code, Micro QR, Code, MaxiCode, Data Matrix
Paper Width	80 mm
Max Roll Diameter	50 mm
Paper Loading	Easy paper loading
Emulation	ESC/POS
Connectors	USB Type-C port
Wired Communication	USB (device)
OS Compatibility	iOS, Android, Windows
Bluetooth (optional)	BT version 4.2 Low Energy
Wireless (optional)	Wi-Fi IEEE 802.11 b/g/n
LED Indication	Paper end, Cover open, Overheating
Audio Features	Electromagnetic buzzer
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 9 V, 1.3 A
Battery	Rechargeable Li-Ion battery, 7.4 V, 2000 mAh
Reliability	50 km (thermal head), IP54 (Internal test)
Certificates	CE, FCC, VCCI
Dimension W x D x H	106 x 122 x 61 mm
Weight	370 g
Operational Temperature	-10 to 50 °C, 20 to 80 % RH
Storage Temperature	-20 to 60 °C, 10 to 90 % RH
Drop Tested	1.2 m, faces and edges (Internal test)
Other Box Contents	90 cm USB Type-A to Type-C cable, DC 9 V, 1.3 A Power Adapter
Compatible Accessories	Belt clip

